



SYCOR

TECHNOLOGY INC.

Automotive Wire

Type GXL - Primary Wire - Thin Wall SYCOR DESIGNATION - A3NXXXXB-X



CONSTRUCTION:

Stranded copper conductors with cross linked Polyethylene insulation.

TEMPERATURE RATING:

-51°C to 125°C

INSULATION:

Cross linked Polyethylene*
*(XLPE)

APPLICATION:

For use in engine compartments where higher heat resistance is required according to SAE J-1128.

COLOUR:

Available in solid colours and stripes, with optional custom printing and/or numbering.

SPECIFICATIONS:

Meets Ford (MIL-85B) and Chrysler (MS-8900) specifications

Sycor Part Number	Size AWG	Strand	Nominal Insulation Thickness	Nominal O.D.	Approx Weight Lbs./Mf
	20	7/28	.023"	.085"	6.5
	18	16/30	.023"	.092"	8.0
	16	19/29	.023"	.103"	10.5
	14	19/27	.023"	.117"	16.0
	12	19/25	.026"	.142"	24.0
	10	19/23	.031"	.179"	38.0
	8	19/21	.037"	.218"	68.0
	6	37/21	.043"	.285"	112.0

Sycor Advance Wire and Cable

Sycor Technology Inc. Advance Wire and Cable Division

2455 Milltower Court, Mississauga, Ontario L5N 5Z6 Phone: (905) 821-3591, Fax: (905) 821-7260