



# Extra Flexible Marine Battery Cable UL1426

## Description

The marine battery cable UL1426 is rated for UL and CSA applications. With extra flexible tinned copper conductors and PVC insulation, this marine battery cable is flame-retardant and moisture, abrasion, acid and diesel resistant.

## Approvals

UL1232, UL1283, UL1426, UL10269  
UL listed BC-5W2  
UL VW-1  
ASTM B172

## Construction

Stranded class K tinned conductors  
Polyvinyl chloride insulation

## Temperature Rating

105°C - Dry  
75°C - Wet

## Voltage Rating

600V / 1000V



## Application

The marine battery cable UL1426 is typically used for transformers, switchboard panels, control, battery charger cable, electrical circuits, battery cable and as a motor lead hook-up cable.

Sycor Part No.	AWG	Strand	Nom. Insul. Thickness (in)	O.D. (in)	UL Style	AMPS	Approx Weight Lbs./Mft
B0B06266T	6	266 x 30	0.060"	0.342"	UL1232, UL1283, UL10269	118	136
B0B04420T	4	420 x 30	0.060"	0.386"	UL1232, UL1283, UL10269	157	189
B0B02665T	2	665 x 30	0.060"	0.446"	UL1232, UL1283, UL10269	213	292
B0B01836T	1	836 x 30	0.080"	0.520"	UL1232, UL1283, UL10269	246	350
B0B1/01064T	1/0	1064 x 30	0.080"	0.575"	UL1232, UL1283, UL10269	291	450
B0B2/01330T	2/0	1330 x 30	0.080"	0.610"	UL1232, UL1283, UL10269	336	551
B0B3/01672T	3/0	1672 x 30	0.080"	0.685"	UL1232, UL1283, UL10269	392	672
B0B4/02109T	4/0	2109 x 30	0.080"	0.745"	UL1232, UL1283, UL10269	454	820

*\*Additional strandings and gauges available upon request. Please contact us to enquire.*

*\*\*Various UL styles available on request.*

## Value Added Services



Cutting



Re-Spooling



Terminating



Twisting



Printing



Tin Dipping



Striping



Dyeing

## Colour Codes

### Colour

Stock colours 0-9. Custom colours and striped combinations available upon request.



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

[www.sycor.com](http://www.sycor.com) 1-800-268-9444 [sales@sycor.com](mailto:sales@sycor.com)

Sycor International Inc ©All Rights Reserved