



Automotive Wire

Marine Engine & Boat Cable

Construction

Stranded bare or tinned copper conductors.
Polyvinyl Chloride (PVC) insulation.

Application

For use in SAE J-1128 and J-378C applications where greater physical protection is required. For internal or external marine engine compartment wiring under 50 Volts.

Temperature Rating

-40°C to +105°C

Approvals

SAE J-1128, SAE J378



Sycor Part Number	AWG	Strand	Nom. Insul. Thickness (in)	O.D. (in)	Approx Weight Lbs./Mft	SAE
GPTM1816B	18	16/30	.023	.092	7.5	J-1128 & J-378
GPTM1619B	16	19/29	.023	.103	11.0	J-1128 & J-378
GPTM1419B	14	19/27	.023	.117	16.0	J-1128 & J-378
GPTM1219B	12	19/25	.026	.141	24.0	J-1128 & J-378
GPTM1019B	10	19/23	.031	.173	37.0	J-1128 & J-378
GPTM0819B	8	19/21	.037	.215	59.0	J-1128 & J-378

Colour Codes



Value Added Services



Cutting



Striping



Re-Spooling



Printing



Dyeing



Twisting

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved