



# Polyolefin Dual Wall Adhesive-Lined 2:1 - Heat Shrink Tubing

## Description

Sycor's dual wall adhesive-lined polyolefin heat shrink tubing is unlike any other cable management product. Once heat is applied the adhesive-lined polyolefin melts to its intended source, ensuring a snug, tight fit.

## Approvals

UL 224 VW-1 (Except transparent)  
MIL-DTL-23053/4  
CSA C22.2 (Available by request)

## Construction

Dual wall adhesive-lined polyolefin (PO) heat shrinkable tubing

## Temperature Rating

-55°C to 135°C  
-55°C to 125°C (UL)  
Shrinks at 90°C

## Application

Sycor's dual wall adhesive-lined polyolefin heat shrink tubing is flame retardant, moisture resistant and chemical resistant. This amazing dual wall heat shrink is typically used on wire harnesses, over connectors and within automobile applications.

## Shrink Ratio

2:1




Sycor Part No	Size AWG	Expanded I.D		Recovered I.D		Class	Colours Available
		inches	mm	inches	mm		
T0K.125AL	1/8"	0.125	3.18	0.063	1.6	2	BK
T0K.250AL	1/4"	0.25	6.35	0.125	3.18	2	BK
T0K.375AL	3/8"	0.375	9.53	0.187	4.75	2	BK
T0K.500AL	1/2"	0.5	12.7	0.25	6.35	2	BK
T0K.750AL	3/4"	0.75	19.05	0.375	9.53	2	BK
T0K1.00AL	1"	1	25.4	0.5	12.7	2	BK
T0K1.50AL	1-1/2"	1.5	38.1	0.75	19.05	2	BK

## Value Added Services



Cutting

## Colour Codes



\*Other colours may be available by special order

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

[www.sycor.com](http://www.sycor.com) 1-800-268-9444 [sales@sycor.com](mailto:sales@sycor.com)

Sycor International Inc ©All Rights Reserved