



MIL-W-22759/15 - SAE AS22759/15, 600V, Lightweight FEP

Description

Mil-W-22759/15 has silver plated high strength copper alloy conductor. With a lightweight FEP construction Mil-W-22759/15 is perfect for applications requiring additional protection against cut-through and abrasion.

Approvals

Mil-W-22759/15
SAE AS22759/15

Construction

Stranded silver plated high strength copper alloy conductor
Extruded FEP light weight insulation
PVDF Jacket

Temperature Rating

135°C

Voltage Rating

600V



Application

Mil-W -22759/15 is typically used in commercial, aerospace and military environments. Mil-W-22759/15 is a strong alternative for environments subject to heavy moisture and smoke.



Sycor Part No.	AWG	Stranding	Conductor Dia. (in)		Insulation Dia. (in)		Approx Weight Lbs./Mft.	Mil-Spec. Designation
			Min	Max	Min	Max		
M22759/15-2619	26	19/38	.018"	.020"	.035"	.039"	1.75	SAE AS22759/15
M22759/15-2419	24	19/36	.023"	.024"	.040"	.044"	2.42	SAE AS22759/15
M22759/15-2219	22	19/34	.029"	.031"	.045"	.051"	3.59	SAE AS22759/15
M22759/15-2019	20	19/32	.037"	.039"	.053"	.059"	5.22	SAE AS22759/15

Additional strandings and gauges available upon request. Please contact us to enquire.

Value Added Services



Cutting



Re-Spooling



Terminating



Twisting

Colour Codes

Colour

Stock colours 0-9. Custom colours and striped combinations available upon request.



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved