



MIL-W-22759/30 - SAE AS22759/30, 600V, PTFE & Polyimide

Description

Mil-W-22759/30 has a silver plated conductor which makes this cable excellent for continuous operation in demanding environments.

Approvals

Mil-W-22759/30
SAE AS22759/30

Construction

Stranded silver plated high strength copper alloy conductor
Extruded PTFE insulation
Polyimide hard coat Jacket

Temperature Rating

200°C

Voltage Rating

600V



Application

Mil-W-22759/30 has a hard coat that has exceptional break strength. Mil-W-22759/30 also provides extra mechanical toughness, which is a strong solution for demanding commercial and aerospace environments.



Sycor Part No.	AWG	Stranding	Conductor Dia. (in)	Insulation Dia. (in)		Approx Weight Lbs./Mft.	Mil-Spec. Designation
				Min	Max		
M22759/30-2807	28	7/36	.015"	.032"	.036"	1.27	SAE AS22759/30
M22759/30-2619	26	19/38	.019"	.037"	.041"	1.8	SAE AS22759/30
M22759/30-2419	24	19/36	.024"	.042"	.046"	2.47	SAE AS22759/30
M22759/30-2219	22	19/34	.030"	.048"	.052"	3.51	SAE AS22759/30
M22759/30-2019	20	19/32	.038"	.057"	.061"	5.24	SAE AS22759/30

Additional standing and gauges available upon request. Please contact us to enquire.

Value Added Services



Cutting



Re-Spooling



Terminating



Twisting

Colour Codes

Colour

Stock colours 0-9. Custom colours and striped combinations available upon request.



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved