



MIL-W-22759/35 - SAE AS22759/35, 600V, XL-ETFE

Description

Mil-W-22759/35 is equipped with high strength silver alloy, XL-ETFE insulation and jacket for added protection. Mil-W-22759/35 construction provides reliable protection when abrasion is present.

Approvals

Mil-W-22759/35
SAE AS22759/35

Construction

Stranded Silver plated high strength copper alloy conductor
Cross linked modified ETFE insulation
Cross linked ETFE jacket

Temperature Rating

200°C

Voltage Rating

600V



Application

Mil-W-22759/35 is a strong solution for applications involving commercial, military, government or aerospace environments. Mil-W-22759/35 is a reliable choice for mechanically tough applications that are subject to harsh settings.



Sycor Part No.	AWG	Stranding	Nom Dia. (in)	Approx Weight Lbs./Mft.	Mil-Spec. Designation
M22759/35-2619	26	19/38	.040"	1.7	SAE AS22759/35
M22759/35-2419	24	19/36	.045"	2.3	SAE AS22759/35
M22759/35-2219	22	19/34	.050"	3.3	SAE AS22759/35
M22759/35-2019	20	19/32	.058"	4.8	SAE AS22759/35

Additional standing and gauges available upon request. Please contact us to enquire.

Value Added Services



Cutting



Re-Spooling



Terminating



Twisting

Colour Codes

Colour

Stock colours 0-9. Custom colours and striped combinations available upon request.



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved