



MIL-W-22759/43 - SAE AS22759/43, 600V, XL-ETFE

Description

Mil-W-22759/43 is constructed with high strength nickel plated copper and dual-layer cross linked ETFE insulation, provides a reliable construction that's built to perform in demanding conditions.

Approvals

Mil-W-22759/43
SAE AS22759/43

Construction

Stranded nickel plated high strength copper alloy conductor
Cross linked modified ETFE dual insulation
Cross linked ETFE jacket
Treated aromatic polyamide braid

Temperature Rating

200°C

Voltage Rating

600V



Application

Mil-W-22759/43 is a military cable that's designed for commercial or aerospace applications. Mil-W-22759/43 is also a perfect choice for applications requiring flexibility and durability.



Sycor Part No.	AWG	Stranding	Nom Dia. (in)	Approx Weight Lbs./Mft.	Mil-Spec. Designation
M22759/43-2619	26	19/38	.040"	1.7	SAE AS22759/43
M22759/43-2419	24	19/36	.045"	2.3	SAE AS22759/43
M22759/43-2219	22	19/34	.050"	3.2	SAE AS22759/43
M22759/43-2019	20	19/32	.058"	4.7	SAE AS22759/43
M22759/43-1819	18	19/30	.070"	7.2	SAE AS22759/43
M22759/43-1619	16	19/29	.077"	9	SAE AS22759/43
M22759/43-1419	14	19/27	.094"	13.8	SAE AS22759/43
M22759/43-1237	12	37/28	.111"	20.5	SAE AS22759/43
M22759/43-1037	10	37/26	.134"	32.4	SAE AS22759/43
M22759/43-08133	8	133/29	.195"	61.9	SAE AS22759/43

Additional standing and gauges available upon request. Please contact us to enquire.

Colour Codes

Colour

Stock colours 0-9. Custom colours and striped combinations available upon request.



Value Added Services



Cutting



Re-Spooling



Terminating



Twisting

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved