

### Construction:

- Stranded silver plated copper conductor
- Extruded polytetrafluoroethylene (PTFE)
- Silver plated copper braid 85% coverage
- White PTFE tape wrapped jacket

### Ratings / Approvals:

SAE AS22759  
200°C, 600 Volts



### Value Added Services



Cutting



Re-Spooling



Terminating

### Colour

0-9 colours and striped combinations available upon request.

| Part Number | Number of Conductors | AWG / Stranding | Primary Diameter | Shield Diameter | Nominal Diameter |
|-------------|----------------------|-----------------|------------------|-----------------|------------------|
| WCRC06-0126 | 1                    | 26 19/38        | .038"            | .054"           | .072"            |
| WCRC06-0226 | 2                    | 26 19/38        | .038"            | .092"           | .116"            |
| WCRC06-0326 | 3                    | 26 19/38        | .038"            | .098"           | .123"            |
| WCRC06-0426 | 4                    | 26 19/38        | .038"            | .108"           | .135"            |
| WCRC06-0124 | 1                    | 24 19/36        | .043"            | .059"           | .085"            |
| WCRC06-0224 | 2                    | 24 19/36        | .043"            | .102"           | .128"            |
| WCRC06-0324 | 3                    | 24 19/36        | .043"            | .109"           | .134"            |
| WCRC06-0424 | 4                    | 24 19/36        | .043"            | .120"           | .144"            |
| WCRC06-0122 | 1                    | 22 19/34        | .049"            | .065"           | .090"            |
| WCRC06-0222 | 2                    | 22 19/34        | .049"            | .114"           | .141"            |
| WCRC06-0322 | 3                    | 22 19/34        | .049"            | .122"           | .143"            |
| WCRC06-0422 | 4                    | 22 19/34        | .049"            | .135"           | .159"            |
| WCRC06-0120 | 1                    | 20 19/32        | .058"            | .074"           | .098"            |
| WCRC06-0220 | 2                    | 20 19/32        | .058"            | .132"           | .158"            |
| WCRC06-0320 | 3                    | 20 19/32        | .058"            | .141"           | .164"            |
| WCRC06-0420 | 4                    | 20 19/32        | .058"            | .156"           | .181"            |
| WCRC06-0118 | 1                    | 18 19/30        | .068"            | .084"           | .109"            |
| WCRC06-0218 | 2                    | 18 19/30        | .068"            | .152"           | .176"            |
| WCRC06-0318 | 3                    | 18 19/30        | .068"            | .163"           | .188"            |
| WCRC06-0418 | 4                    | 18 19/30        | .068"            | .181"           | .207"            |
| WCRC06-0116 | 1                    | 16 19/29        | .075"            | .091"           | .117"            |
| WCRC06-0216 | 2                    | 16 19/29        | .075"            | .166"           | .192"            |
| WCRC06-0316 | 3                    | 16 19/29        | .075"            | .178"           | .202"            |
| WCRC06-0416 | 4                    | 16 19/29        | .075"            | .198"           | .224"            |
| WCRC06-0114 | 1                    | 14 19/27        | .090"            | .106"           | .131"            |
| WCRC06-0214 | 2                    | 14 19/27        | .090"            | .196"           | .221"            |
| WCRC06-0314 | 3                    | 14 19/27        | .090"            | .210"           | .237"            |
| WCRC06-0414 | 4                    | 14 19/27        | .090"            | .233"           | .263"            |
| WCRC06-0112 | 1                    | 12 19/25        | .111"            | .127"           | .151"            |
| WCRC06-0212 | 2                    | 12 19/25        | .111"            | .238"           | .262"            |

*\*Additional strandings and gauges available upon request. Please contact us to enquire.*

*\*\*Replaces MIL-C-27500*