

### Construction:

- Stranded silver plated copper conductor
- Extruded polytetrafluoroethylene (PTFE)
- Silver plated copper braid 85% coverage
- White extruded FEP jacket

### Ratings / Approvals:

SAE AS22759  
200°C, 600 Volts



### Value Added Services



Cutting



Re-Spooling



Terminating

### Colour

0-9 colours and striped combinations available upon request.

Part Number	Number of Conductors	AWG / Stranding	Primary Diameter	Shield Diameter	Nominal Diameter
WCRC09-0126	1	26 19/38	.038"	.054"	.073"
WCRC09-0226	2	26 19/38	.038"	.092"	.110"
WCRC09-0326	3	26 19/38	.038"	.098"	.116"
WCRC09-0426	4	26 19/38	.038"	.108"	.126"
WCRC09-0124	1	24 19/36	.043"	.059"	.075"
WCRC09-0224	2	24 19/36	.043"	.102"	.118"
WCRC09-0324	3	24 19/36	.043"	.109"	.127"
WCRC09-0424	4	24 19/36	.043"	.120"	.138"
WCRC09-0122	1	22 19/34	.049"	.065"	.083"
WCRC09-0222	2	22 19/34	.049"	.114"	.132"
WCRC09-0322	3	22 19/34	.049"	.122"	.138"
WCRC09-0422	4	22 19/34	.049"	.135"	.153"
WCRC09-0120	1	20 19/32	.058"	.074"	.090"
WCRC09-0220	2	20 19/32	.058"	.132"	.150"
WCRC09-0320	3	20 19/32	.058"	.141"	.156"
WCRC09-0420	4	20 19/32	.058"	.156"	.180"
WCRC09-0118	1	18 19/30	.068"	.084"	.102"
WCRC09-0218	2	18 19/30	.068"	.152"	.176"
WCRC09-0318	3	18 19/30	.068"	.163"	.187"
WCRC09-0418	4	18 19/30	.068"	.181"	.205"
WCRC09-0116	1	16 19/29	.075"	.091"	.109"
WCRC09-0216	2	16 19/29	.075"	.166"	.190"
WCRC09-0316	3	16 19/29	.075"	.178"	.202"
WCRC09-0416	4	16 19/29	.075"	.198"	.222"
WCRC09-0114	1	14 19/27	.090"	.106"	.124"
WCRC09-0214	2	14 19/27	.090"	.196"	.220"
WCRC09-0314	3	14 19/27	.090"	.210"	.235"
WCRC09-0414	4	14 19/27	.090"	.233"	.258"
WCRC09-0112	1	12 19/25	.111"	.127"	.145"
WCRC09-0212	2	12 19/25	.111"	.238"	.262"

*\*Additional strandings and gauges available upon request. Please contact us to enquire.*

*\*\*Replaces MIL-C-27500*