

Construction:

- Stranded tin plated copper conductor
- Extruded ETFE
- Tin plated copper braid 85% coverage
- White extruded ETFE jacket

Ratings / Approvals:

SAE AS22759
150°C, 600 Volts



Value Added Services



Colour
0-9 colours and striped combinations available upon request.

Part Number	Number of Conductors	AWG / Stranding	Primary Diameter	Shield Diameter	Nominal Diameter
WCTE14-0124	1	24 19/36	.045"	.061"	.077"
WCTE14-0224	2	24 19/36	.045"	.106"	.122"
WCTE14-0324	3	24 19/36	.045"	.113"	.130"
WCTE14-0424	4	24 19/36	.045"	.125"	.143"
WCTE14-0122	1	22 19/34	.052"	.068"	.084"
WCTE14-0222	2	22 19/34	.052"	.120"	.134"
WCTE14-0322	3	22 19/34	.052"	.128"	.145"
WCTE14-0422	4	22 19/34	.052"	.142"	.160"
WCTE14-0120	1	20 19/32	.060"	.076"	.092"
WCTE14-0220	2	20 19/32	.060"	.136"	.152"
WCTE14-0320	3	20 19/32	.060"	.145"	.161"
WCTE14-0420	4	20 19/32	.060"	.161"	.183"
WCTE14-0118	1	18 19/30	.071"	.087"	.103"
WCTE14-0218	2	18 19/30	.071"	.158"	.180"
WCTE14-0318	3	18 19/30	.071"	.169"	.193"
WCTE14-0418	4	18 19/30	.071"	.187"	.211"
WCTE14-0116	1	16 19/29	.079"	.095"	.111"
WCTE14-0216	2	16 19/29	.079"	.174"	.198"
WCTE14-0316	3	16 19/29	.079"	.180"	.208"
WCTE14-0416	4	16 19/29	.079"	.207"	.231"
WCTE14-0114	1	14 19/27	.093"	.109"	.127"
WCTE14-0214	2	14 19/27	.093"	.202"	.226"
WCTE14-0314	3	14 19/27	.093"	.216"	.240"
WCTE14-0414	4	14 19/27	.093"	.241"	.265"
WCTE14-0112	1	12 19/25	.114"	.130"	.148"
WCTE14-0212	2	12 19/25	.114"	.244"	.268"
WCTE14-0312	3	12 19/25	.114"	.262"	.292"
WCTE14-0412	4	12 19/25	.114"	.295"	.325"

**Additional strandings and gauges available upon request. Please contact us to enquire.*

***Replaces MIL-C-27500*