



MIL-W-22759/11 - SAE AS22759/11, 600V, PTFE

Description

Extruded PTFE insulated hook-up wire for aircraft or commercial appliances & equipment

Approvals

Mil-W-22759/11
SAE AS22759/11

Construction

Stranded silver plated copper conductors
Extruded Polytetrafluoroethylene (PTFE) insulation

Temperature Rating

200°C

Voltage Rating

600V

Application

Rugged aerospace and commercial applications where abrasion is a concern. It has low weight and small dimensions and is resistant to high temperatures with low flame propagation.



Sycor Part No	AWG	Stranding	Nominal Insulation Thickness		Nominal O.D.		Approx Weight	
			inches	mm	inches	mm	Lbs/1000ft	kg/km
B0Q2807S	28	7/36	0.009	0.2	0.033	0.8	2	3
B0Q2619S	26	19/38	0.01	0.3	0.038	1	2	3
B0Q2419S	24	19/36	0.01	0.3	0.043	1.1	3	4
B0Q2219S	22	19/34	0.009	0.2	0.049	1.2	4	6
B0Q2019S	20	19/32	0.01	0.3	0.058	1.5	6	9
B0Q1819S	18	19/30	0.01	0.3	0.068	1.7	8	12
B0Q1619S	16	19/29	0.01	0.3	0.075	1.9	10	15
B0Q1419S	14	19/27	0.011	0.3	0.09	2.3	15	22
B0Q1219S	12	19/25	0.013	0.3	0.111	2.8	23	34
B0Q1037S	10	37/26	0.015	0.4	0.139	3.5	35	52
B0Q08133S	8	133/29	0.019	0.5	0.204	5.2	66	98

Additional strandings and gauges available upon request. Please contact us to enquire.

Value Added Services



Cutting



Re-Spooling



Terminating



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved