



MIL-W-22759/16, Tefzel

150°C, 600 Volts

Description

Extruded ETFE insulated hook-up wire for aircraft or commercial appliances & equipment

Approvals

MIL-W-22759/16
SAE AS22759/16

Construction

Stranded tin plated copper conductors
Extruded ETFE*®
*Tefzel® (Ethylene Tetrafluoroethylene)(ETFE) insulation

Temperature Rating

150°C

Voltage Rating:

600 Volts

Application:

Rugged aerospace and commercial applications where abrasion is a concern. It has low weight and small dimensions and is resistant to high temperatures with low flame propagation



Sycor Part No	Size AWG	Stranding	Insulation Thickness	Nominal O.D.	Approx Weight Lbs./Mft.
A0G2419T	24	19/36	.010	.045	2.60
A0G2219T	22	19/34	.010	.052	3.70
A0G2019T	20	19/32	.010	.060	5.40
A0G1819T	18	19/30	.010	.071	7.90
A0G1619T	16	19/29	.010	.078	10.00
A0G1419T	14	19/27	.012	.093	15.00
A0G1237T	12	37/28	.013	.115	22.00
A0G1037T	10	37/26	.013	.135	35.00
A0G08133T	8	133/29	.015	.199	63.00
A0G06133T	6	122/27	.019	.250	100.00
A0G04133T	4	122/25	.020	.312	157.00
A0G02665T	2	655/30	.024	.388	239.00

Color

Stock colors 0-9. Custom colors and striped combinations available upon request.

Color codes



Additional strandings and gauges available upon request.

Value Added Services



Cutting



Re-Spooling



Terminating

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved