



UL 3357 Test Lead

1500V – 10000V Rubber/PVC

Description

This cable is frequently used as test probe leads for electrical measuring and test equipment.

Approvals

UL 3357

Construction

20 - 18 AWG fully annealed stranded tinned copper conductor

Single conductor

Polyvinyl chloride (PVC) or rubber insulation

Temperature Rating

Rubber: -40°C to +90°C

PVC: -30°C to +105°C



Voltage Ratings

1500V

3000V

5000V

10000V

Application

Test equipment

Oscilloscopes




Sycor Part No	Size AWG	Stranding	Nominal Insulation		Nominal O.D		Material	Working Voltage
			inches	mm	inches	mm		
G2A2041T-1.5	20	41	0.04	0.1312	0.125	0.4101	EDPM	1500V
G2A2041T-3	20	41	0.047	0.1542	0.14	0.4593	EDPM	3000V
G2A1865T-5	18	65	0.045	0.1476	0.145	0.4757	EDPM	5000V
G2A1865T-10	18	65	0.088	0.2887	0.23	0.7546	EDPM	10000V
G2B1865T-5	18	65	0.047	0.1542	0.14	0.4593	PVC	5000V

Additional standins and gauges available may be upon request. Please contact us to enquire.

Color

Stock colors 0-11, custom colors, and striped combinations may be available upon request.


Color Codes



Value Added Services



Cutting



Stripping



Re-Spooling



Terminating



Tin Dipping

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved