



DLO – (Diesel Locomotive 2kv) Industrial Flexible Power Cord

Description

Sycor's DLO (Diesel locomotive) cable is a portable or fixed power cable. DLO (Diesel locomotive) is a medium voltage cable that's suitable for motor leads and case wiring.

Construction

Extra flexible, tinned annealed stranded copper conductor
Single separator between conductor and insulation
Ethylene propylene rubber (EPR) insulation

Approvals

UL/CSA approved
Nema WC8
ICEA S-68-516

Temperature Rating
90°C

Voltage Rating
2kv



Application:

Sycor's DLO (Diesel locomotive) cable is typically used in drilling rigs, railroads, transit cars and electrical diesel locomotive applications. Sycor's DLO (Diesel locomotive) cable can also be used as a portable cord for water heater leads, jumper cables and even for electrical earth moving equipment.



Sycor Part No	AWG	Stranding	# of COND.	NOM. Insulation	NOM O.D	Approx Weight Lbs./Mft.
DLO1027	10	27/24	1	.0455"	.026"	60
DLO0837	8	37/24	1	.060"	.034"	95
DLO0661	6	61/24	1	.060"	.040"	145
DLO04105	4	105/24	1	.060"	.046"	205
DLO02154	2	154/24	1	.060"	.052"	295
DLO01224	1	224/24	1	.080"	.065"	440
DLO1/0280	1/0	280/24	1	.080"	.069"	515
DLO2/0329	2/0	329/24	1	.080"	.073"	580
DLO3/0456	3/0	456/24	1	.080"	.081"	770
DLO4/0551	4/0	551/24	1	.080"	.087"	930
DLO262646	262 MCM	646/24	1	.095"	1.00"	1130
DLO313777	313 MCM	777/24	1	.095"	1.06"	1295
DLO373925	373 MCM	925/24	1	.095"	1.11"	1545
DLO4441110	444 MCM	1110/24	1	.095"	1.23"	1820
DLO5451332	545 MCM	1332/24	1	.120"	1.34"	2195
DLO6461600	646 MCM	1600/24	1	.120"	1.45"	2560
DLO11111924	1111 MCM	1924/24	1	.120"	1.50"	3050

Value Added Services

Colour codes




Cutting



Re-Spooling



Terminating



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com