



Portable Cord

Type SV – Rubber Jacketed

Type SVT – Thermoplastic Jacketed

Type SVO – Neoprene Jacketed

Type SV - Rubber Jacketed



Sycor Part No	No. of Cond.	Size AWG	Stranding	Insulation Thick.		Jacket Thickness		O.D		Ampacity	Approx Weight	
				inches	mm	inches	mm	inches	mm		lbs/1000ft	KGs/KM
SV182	2	18	41	0.016	0.4	0.03	0.762	0.245	6.223	10	39	58
SV183	3	18	41	0.016	0.4	0.03	0.762	0.255	6.477	10	46	68

Construction

Extra flexible stranded copper conductors with separator and color coded insulation. Cabled with filler and separator. UL & CSA listed.

Temperature Rating

-40°C to 60°C

Insulation

EPDM or PVC

Application

Vacuum cleaners, domestic food mixers, office equipment and other light duty applications.

Voltage Rating

300 V

Jacket

Rubber, Black

Type SVT - Thermoplastic Jacketed



Sycor Part No	No. of Cond.	Size AWG	Stranding	Insulation Thick.		Jacket Thickness		O.D		Ampacity	Approx Weight	
				inches	mm	inches	mm	inches	mm		lbs/1000ft	KGs/KM
SVT182	2	18	41	0.015	0.38	0.03	0.76	0.235	5.97	10	35	52
SVT183	3	18	41	0.015	0.38	0.03	0.76	0.24	6.1	10	40	59
SVT173	3	17	52	0.015	0.38	0.03	0.76	0.27	6.86	10	42	63
SVT162	2	16	65	0.015	0.38	0.03	0.76	0.25	6.35	10	45	67
SVT163	3	16	65	0.015	0.38	0.03	0.76	0.269	6.83	10	48	71

Construction

Extra flexible stranded copper conductors with separator and color coded insulation. Cabled with filler and separator. UL & CSA listed.

Temperature Rating

-20°C to 60°C

Insulation

PVC (Polyvinyl Chloride)

Application

Vacuum cleaners, domestic food mixers, office equipment and other light duty applications.

Voltage Rating

300 V

Jacket

PVC (Polyvinyl Chloride)

Type SVO - Neoprene Jacketed



Sycor Part No	No. of Cond.	Size AWG	Stranding	Insulation Thick.		Jacket Thickness		O.D		Ampacity	Approx Weight	
				inches	mm	inches	mm	inches	mm		lbs/1000ft	KGs/KM
SVO182	2	18	41	0.015	0.38	0.03	0.762	0.225	5.72	10	34	50
SVO183	3	18	41	0.015	0.38	0.03	0.762	0.235	5.97	10	40	60

Construction

Extra flexible stranded copper conductors with separator and color coded insulation. Cabled with filler and separator. UL & CSA listed.

Temperature Rating

-40°C to 90°C

Insulation

Color coded EPDM

Application

Vacuum cleaners, domestic food-mixers, office equipment when exposed to acid and oils.

Voltage Rating

300 V

Jacket

Neoprene

Value Added Services



Cutting



Re-Spooling



Terminating



Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved