



Portable Cord Type SJT

Description

Sycor's SJT (Situational Judgment Test) portable power cord is oil, moisture, alkali, ozone resistant. The portable cord is also extremely flexible and versatile in indoor or outdoor settings.

Construction

Extra flexible stranded copper conductors with separator and color coded thermoplastic insulation.

Cabled with filler, separator, and overall thermoplastic jacket.

Insulation

Polyvinyl Chloride

Approvals

UL/CSA approved

Temperature Rating

60°C or 105°C
-20°C to +60°C (105°C)

Voltage Rating

300V
AMPS per NEC Art.400

Jacket

Polyvinyl Chloride, Black

Application:

Sycor's Type SJT portable cord is a perfect solution for applications involving electric mixers, polishers, washing machines and portable appliance.

Cold Bend:

Meets UL cold bend test at -35°C



Sycor Part No	No of Cond.	Size AWG	Stranding	Insulation Thick.	Jack. Thickness	O.D.	Ampacity	Approx Weight Lbs./Mft.
Stationary Service -60°C								
SJT 182-60	2	18	16x30	.030	.030	.293	10	49
SJT 183-60	3	18	16x30	.030	.030	.312	10	38
SJT 162-60	2	16	26x30	.030	.030	.314	13	56
SJT 163-60	3	16	26x30	.030	.030	.334	13	72
Constant Service -105°C - Extra Flexible Stranding								
SJT 182-105	2	18	41x34	.030	.030	.293	10	49
SJT 183-105	3	18	41x34	.030	.030	.312	10	58

Value Added Services



Cutting



Re-Spooling



Terminating

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

www.sycor.com 1-800-268-9444 sales@sycor.com

Sycor International Inc ©All Rights Reserved