



# Portable Cord

Type SV – Rubber Jacketed  
 Type SVT – Thermoplastic Jacketed  
 Type SVO – Neoprene Jacketed

## Type SV - Rubber Jacketed

Sycor Part No	No of Cond.	Size AWG	Stranding	Insulation Thickness	Jacket Thickness	O.D.	Ampacity	Approx Weight Lbs./Mft.
SV182	2	18	41/34	.016	.030	.245	10	39
SV183	3	18	41/34	.016	.030	.255	10	46

**Construction**

Extra flexible stranded copper conductors with separator and color coded insulation. Cabled with filler and separator. UL & CSA listed.

**Temperature Rating**

-40°C to 60°C

**Voltage Rating**

300 V

**Insulation**

Rubber

**Jacket**

Rubber, Black

**Application**

Vacuum cleaners, domestic food mixers, office equipment and other light duty applications.

## Type SVT - Thermoplastic Jacketed

Sycor Part No	No of Cond.	Size AWG	Stranding	Insulation Thickness	Jacket Thickness	O.D.	Ampacity	Approx Weight Lbs./Mft.
SVT182	2	18	41	0.015"	0.030"	0.240"	10	31
SVT183	3	18	41	0.015"	0.030"	0.255"	10	38
SVT172	2	17	52	0.015"	0.030"	0.242"	10	36
SVT173	3	17	52	0.015"	0.030"	0.280"	10	42
SVT162	2	16	65	0.015"	0.030"	0.280"	13	37
SVT163	3	16	65	0.015"	0.030"	0.290"	13	48

**Construction**

Extra flexible stranded copper conductors with separator and color coded insulation. Cabled with filler and separator. UL & CSA listed.

**Temperature Rating**

-20°C to 60°C

**Voltage Rating**

300 V

**Insulation**

PVC (Polyvinyl Chloride)

**Jacket**

PVC (Polyvinyl Chloride)

**Application**

Vacuum cleaners, domestic food mixers, office equipment and other light duty applications.



# Portable Cord

Type SV – Rubber Jacketed

Type SVT – Thermoplastic Jacketed

Type SVO – Neoprene Jacketed

## Type SVO - Neoprene Jacketed

Sycor Part No.	No of Cond.	Size AWG	Stranding	Insulation Thickness	Jacket Thickness	O.D.	Ampacity	Approx Weight Lbs./Mft.
SVO182	2	18	41/34	.016	.030	.245	10	39
SVO183	3	18	41/34	.016	.030	.255	10	46

### Construction

Extra flexible stranded copper conductors with separator and color coded insulation. Cabled with filler and separator. UL & CSA listed.

### Insulation

Color coded EPDM

### Jacket

Neoprene

### Temperature Rating

-40°C to 90°C

### Voltage Rating

300 V

### Application

Vacuum cleaners, domestic food-mixers, office equipment when exposed to acid and oils.

## Value Added Services



Cutting



Re-Spooling



Terminating

Sycor Technology Inc., 1-2220 Argentia Road, Mississauga ON L5N 2K7

[www.sycor.com](http://www.sycor.com) 1-800-268-9444 [sales@sycor.com](mailto:sales@sycor.com)

Sycor International Inc ©All Rights Reserved